



Southeastern Stud & Components, Inc.

Material Certification - code approvals and performance:

Structural framing standards	Interior drywall framing with ProSTUD™ Drywall Framing System	
<p>AISI "North American Specification for the Design of Cold-Formed Steel Structural Members, 2001 with 2004 supplement"</p> <p>ASTM C955 Load-bearing steel framing ASTM C1007 Installation ASTM A1003 Material specification for steel sheet requirements</p> <p>Protective coating standards</p> <p>ASTM A924 Metallic coated hot-dip process ASTM A653 Zinc coated hot-dip process ASTM A463 Aluminum coated hot-dip process ASTM A591 Zinc coated, light coating mass applications ASTM A792 55% aluminum-zinc alloy-coated hot-dip process ASTM A875 Zinc-5% aluminum alloy-coated hot-dip process</p> <p>Additional code approvals</p> <p>SSMA (Steel Stud Manufacturers Association) ICC-ES ER-4943P</p> <p>SES is a member of the Steel Stud Manufacturer's Association (SSMA)</p>	<p>AISI "North American Specification for the Design of Cold-Formed Steel Structural Members, 2001 with 2004 supplement"</p> <p>ASTM A653 Coating specification ASTM A1003 Material specification ASTM C645 Non-structural steel framing members ASTM C754 Installation ASTM E119 Fire tests ASTM E72 Strength tests ASTM E90 Airborne sound transmission</p> <p>UL® Underwriters Laboratories Testing Standard</p> <p>UL263 "Fire Tests of Building Construction/Materials" Over 40 UL designs for ProSTUD</p> <p>See UL file number R26034 for additional information. Fire designs include U419, V450 & V438.</p> <p>Additional code approvals</p> <p>IBC International Building Code IAPMO ES Pending ICC-ES Pending</p> <p><small>**UL and UL Design are service marks of Underwriters Laboratories, Inc.</small></p>	<p>Independent product testing and certification</p> <p>Sound ratings: Western Electro - Acoustic Laboratory</p> <p>Fire testing: Underwriters Laboratories Inc.</p> <p>Structural testing: (STAR) Structural Testing and Research Inc.</p> <p>Structural analysis: CTLGroup</p>
		Metal lath & accessories
		<p>ASTM C847 Metal lath ASTM C841 Installation of interior lathing & furring ASTM C1063 Installation of lathing & furring ASTM A653 Zinc coated hot-dip process ASTM C1047 Accessories standards - control joints ASTM A924 Metallic coated hot-dip process ASTM UUB790A APB type 1, grade D, style 2 CE 240.01 Furring (metal) lating & plastering ML/SFA-920 Guide specs for metal lathing & furring</p>



USGBC and related logo is a trademark owned by the U.S. Green Building Council and is used by permission

Green benefits and recycled content:

LEED Credit MR 2 Construction Waste Management - SES products are manufactured from coldformed steel. Steel is 100% recyclable, which helps divert debris from the waste stream. The contribution to LEED must be calculated by the contractor based on weight or volume.

LEED Credit MR 4 Recycled Content - SES's steel products have a minimum of 25.5% post-consumer recycled content, and 6.8% pre-consumer. If you wish to report a higher number for your project or seek Credit MR 5 regional materials, please contact Tech Support at 888-437-3244 or visit www.sestud.com